

APRILIA SPORTCITY CUBE 300: TECHNICAL DATA

Engine	Single cylinder 4 stroke
Displacement	278 cm ³
Bore and Stroke	75 mm x 63 mm
Fuel	Unleaded fuel
Compression ratio	11:1
Max power	16,1 kw (21,9 hp) a 7.250 rpm
Max torque	23 Nm a 6.000 rpm
Fuel system	Electronic fuel injection
Starting	Electric
Generator	380 W
Ignition	Inductive electronic ignition with variable timing
Lubrication	Wet sump, mechanical orbital pump
Gearbox	Automatic variator
Clutch	Automatic centrifugal
Primary drive	V belt
Final drive	Gearbox
Frame	Single cradle frame in high tensile strength steel
Front suspension	Hydraulic fork, wheel travel 100 mm
Rear suspension	Engine unit acting as swingarm. double hydraulic shock absorber with adjustable spring preload, wheel travel 80 mm
Brakes	Front D Ø 260 mm twin disc with twin piston calipers Rear D Ø 220 mm with single piston caliper
Wheels	Light alloy Front 2,75 x 15" Rear 3,00 x 15"
Tyres	Tubeless Front 120/70 15" Rear 130/80 15"
Dimensions	Length 2000 mm Width 730 mm Wheelbase 1375 mm Seat height 790 mm
Tank capacity	8,5L (1,5L reserve)
Under seat storage	Large enough to hold a Jet helmet Aprilia
Emissions	Euro 3
Accessories	Top Box City 35L, Top Box New Concept 32L embossed, Kit windshield, Kit sportive windshield, Cover Top Box City 35L, Seat cushion Top Box City 35L, Seat cushion Top Box New Concept 32L, Anti-vibration weights bars
Colours 2009	Aprilia Black, Escape Grey

Technical specifications are correct at time of printing, and are subject to change without notice.